





Application for issuing a Co-license

Original license holder : Ningbo Ginlong technologies Co., Ltd.
 Original license Number : R 50331629
Certified Product(s) : PV-Inverter (Grid-connected PV Inverter)
Certified type designation : Solis-20K, Solis-25K, Solis-30K, Solis-40K-HV
New type designation for Co-license : CSI-20KTL-GI-FL, CSI-25KTL-GI-FL, CSI-30KTL-GI-FL, CSI-40KTL-GI-HFL.....
 Co-license holder's name : Canadian Solar Inc.
 And address : 545 Speedvale Avenue West, Guelph, Ontario, N1K 1E6 Canada
 And Contact person with phone no : Hongyu Tian Tel: +8651268966148 Mobile: +8613901557147

Please insert rating label for the Co-license product here::

 CanadianSolar	 CanadianSolar	 CanadianSolar	 CanadianSolar																																																																																																																																								
<table border="1"> <tr><td>Model Number</td><td>CSI-20KTL-GI-FL</td></tr> <tr><td>PDC max</td><td>23kW</td></tr> <tr><td>VDC max</td><td>1000V d.c.</td></tr> <tr><td>IDC max(each MPPT)</td><td>18/18/18/18Ad.c.</td></tr> <tr><td>Ipv max short circuit(each MPPT)</td><td>23.4Ad.c.</td></tr> <tr><td>VDC start up</td><td>350V d.c.</td></tr> <tr><td>VDC MPPT range</td><td>200-800V</td></tr> <tr><td>VAC norm</td><td>3-400Va.c.</td></tr> <tr><td>F AC norm</td><td>50Hz</td></tr> <tr><td>P AC max</td><td>22kW</td></tr> <tr><td>I AC max</td><td>33.3Aa.c.</td></tr> <tr><td>PF</td><td>>0.99</td></tr> <tr><td>Ambient temperature</td><td>-25...+60°C (Derating at 45°C)</td></tr> <tr><td>Ingress protection</td><td>IP65</td></tr> <tr><td>Protective class</td><td>Class I</td></tr> <tr><td>Oversvoltage category</td><td>III(MAINS)/II(PV)</td></tr> <tr><td>Certifications</td><td>IEC62109-1/-2</td></tr> </table>	Model Number	CSI-20KTL-GI-FL	PDC max	23kW	VDC max	1000V d.c.	IDC max(each MPPT)	18/18/18/18Ad.c.	Ipv max short circuit(each MPPT)	23.4Ad.c.	VDC start up	350V d.c.	VDC MPPT range	200-800V	VAC norm	3-400Va.c.	F AC norm	50Hz	P AC max	22kW	I AC max	33.3Aa.c.	PF	>0.99	Ambient temperature	-25...+60°C (Derating at 45°C)	Ingress protection	IP65	Protective class	Class I	Oversvoltage category	III(MAINS)/II(PV)	Certifications	IEC62109-1/-2	<table border="1"> <tr><td>Model Number</td><td>CSI-25KTL-GI-FL</td></tr> <tr><td>PDC max</td><td>28kW</td></tr> <tr><td>VDC max</td><td>1000V d.c.</td></tr> <tr><td>IDC max(each MPPT)</td><td>18/18/18/18Ad.c.</td></tr> <tr><td>Ipv max short circuit(each MPPT)</td><td>23.4Ad.c.</td></tr> <tr><td>VDC start up</td><td>350V d.c.</td></tr> <tr><td>VDC MPPT range</td><td>200-800V</td></tr> <tr><td>VAC norm</td><td>3-400Va.c.</td></tr> <tr><td>F AC norm</td><td>50Hz</td></tr> <tr><td>P AC max</td><td>27.5kW</td></tr> <tr><td>I AC max</td><td>41.7Aa.c.</td></tr> <tr><td>PF</td><td>>0.99</td></tr> <tr><td>Ambient temperature</td><td>-25...+60°C (Derating at 45°C)</td></tr> <tr><td>Ingress protection</td><td>IP65</td></tr> <tr><td>Protective class</td><td>Class I</td></tr> <tr><td>Oversvoltage category</td><td>III(MAINS)/II(PV)</td></tr> <tr><td>Certifications</td><td>IEC62109-1/-2</td></tr> </table>	Model Number	CSI-25KTL-GI-FL	PDC max	28kW	VDC max	1000V d.c.	IDC max(each MPPT)	18/18/18/18Ad.c.	Ipv max short circuit(each MPPT)	23.4Ad.c.	VDC start up	350V d.c.	VDC MPPT range	200-800V	VAC norm	3-400Va.c.	F AC norm	50Hz	P AC max	27.5kW	I AC max	41.7Aa.c.	PF	>0.99	Ambient temperature	-25...+60°C (Derating at 45°C)	Ingress protection	IP65	Protective class	Class I	Oversvoltage category	III(MAINS)/II(PV)	Certifications	IEC62109-1/-2	<table border="1"> <tr><td>Model Number</td><td>CSI-30KTL-GI-FL</td></tr> <tr><td>PDC max</td><td>34kW</td></tr> <tr><td>VDC max</td><td>1000V d.c.</td></tr> <tr><td>IDC max(each MPPT)</td><td>18/18/18/18Ad.c.</td></tr> <tr><td>Ipv max short circuit(each MPPT)</td><td>23.4Ad.c.</td></tr> <tr><td>VDC start up</td><td>350V d.c.</td></tr> <tr><td>VDC MPPT range</td><td>200-800V</td></tr> <tr><td>VAC norm</td><td>3-400Va.c.</td></tr> <tr><td>F AC norm</td><td>50Hz</td></tr> <tr><td>P AC max</td><td>33kW</td></tr> <tr><td>I AC max</td><td>47.8Aa.c.</td></tr> <tr><td>PF</td><td>>0.99</td></tr> <tr><td>Ambient temperature</td><td>-25...+60°C (Derating at 45°C)</td></tr> <tr><td>Ingress protection</td><td>IP65</td></tr> <tr><td>Protective class</td><td>Class I</td></tr> <tr><td>Oversvoltage category</td><td>III(MAINS)/II(PV)</td></tr> <tr><td>Certifications</td><td>IEC62109-1/-2</td></tr> </table>	Model Number	CSI-30KTL-GI-FL	PDC max	34kW	VDC max	1000V d.c.	IDC max(each MPPT)	18/18/18/18Ad.c.	Ipv max short circuit(each MPPT)	23.4Ad.c.	VDC start up	350V d.c.	VDC MPPT range	200-800V	VAC norm	3-400Va.c.	F AC norm	50Hz	P AC max	33kW	I AC max	47.8Aa.c.	PF	>0.99	Ambient temperature	-25...+60°C (Derating at 45°C)	Ingress protection	IP65	Protective class	Class I	Oversvoltage category	III(MAINS)/II(PV)	Certifications	IEC62109-1/-2	<table border="1"> <tr><td>Model Number</td><td>CSI-40KTL-GI-HFL</td></tr> <tr><td>PDC max</td><td>45kW</td></tr> <tr><td>VDC max</td><td>1000V d.c.</td></tr> <tr><td>IDC max(each MPPT)</td><td>18/18/18/18Ad.c.</td></tr> <tr><td>Ipv max short circuit(each MPPT)</td><td>23.4Ad.c.</td></tr> <tr><td>VDC start up</td><td>350V d.c.</td></tr> <tr><td>VDC MPPT range</td><td>200-800V</td></tr> <tr><td>VAC norm</td><td>3-480Va.c.</td></tr> <tr><td>F AC norm</td><td>50Hz</td></tr> <tr><td>P AC max</td><td>44kW</td></tr> <tr><td>I AC max</td><td>48.1Aa.c.</td></tr> <tr><td>PF</td><td>>0.99</td></tr> <tr><td>Ambient temperature</td><td>-25...+60°C (Derating at 45°C)</td></tr> <tr><td>Ingress protection</td><td>IP65</td></tr> <tr><td>Protective class</td><td>Class I</td></tr> <tr><td>Oversvoltage category</td><td>III(MAINS)/II(PV)</td></tr> <tr><td>Certifications</td><td>IEC62109-1/-2</td></tr> </table>	Model Number	CSI-40KTL-GI-HFL	PDC max	45kW	VDC max	1000V d.c.	IDC max(each MPPT)	18/18/18/18Ad.c.	Ipv max short circuit(each MPPT)	23.4Ad.c.	VDC start up	350V d.c.	VDC MPPT range	200-800V	VAC norm	3-480Va.c.	F AC norm	50Hz	P AC max	44kW	I AC max	48.1Aa.c.	PF	>0.99	Ambient temperature	-25...+60°C (Derating at 45°C)	Ingress protection	IP65	Protective class	Class I	Oversvoltage category	III(MAINS)/II(PV)	Certifications	IEC62109-1/-2
Model Number	CSI-20KTL-GI-FL																																																																																																																																										
PDC max	23kW																																																																																																																																										
VDC max	1000V d.c.																																																																																																																																										
IDC max(each MPPT)	18/18/18/18Ad.c.																																																																																																																																										
Ipv max short circuit(each MPPT)	23.4Ad.c.																																																																																																																																										
VDC start up	350V d.c.																																																																																																																																										
VDC MPPT range	200-800V																																																																																																																																										
VAC norm	3-400Va.c.																																																																																																																																										
F AC norm	50Hz																																																																																																																																										
P AC max	22kW																																																																																																																																										
I AC max	33.3Aa.c.																																																																																																																																										
PF	>0.99																																																																																																																																										
Ambient temperature	-25...+60°C (Derating at 45°C)																																																																																																																																										
Ingress protection	IP65																																																																																																																																										
Protective class	Class I																																																																																																																																										
Oversvoltage category	III(MAINS)/II(PV)																																																																																																																																										
Certifications	IEC62109-1/-2																																																																																																																																										
Model Number	CSI-25KTL-GI-FL																																																																																																																																										
PDC max	28kW																																																																																																																																										
VDC max	1000V d.c.																																																																																																																																										
IDC max(each MPPT)	18/18/18/18Ad.c.																																																																																																																																										
Ipv max short circuit(each MPPT)	23.4Ad.c.																																																																																																																																										
VDC start up	350V d.c.																																																																																																																																										
VDC MPPT range	200-800V																																																																																																																																										
VAC norm	3-400Va.c.																																																																																																																																										
F AC norm	50Hz																																																																																																																																										
P AC max	27.5kW																																																																																																																																										
I AC max	41.7Aa.c.																																																																																																																																										
PF	>0.99																																																																																																																																										
Ambient temperature	-25...+60°C (Derating at 45°C)																																																																																																																																										
Ingress protection	IP65																																																																																																																																										
Protective class	Class I																																																																																																																																										
Oversvoltage category	III(MAINS)/II(PV)																																																																																																																																										
Certifications	IEC62109-1/-2																																																																																																																																										
Model Number	CSI-30KTL-GI-FL																																																																																																																																										
PDC max	34kW																																																																																																																																										
VDC max	1000V d.c.																																																																																																																																										
IDC max(each MPPT)	18/18/18/18Ad.c.																																																																																																																																										
Ipv max short circuit(each MPPT)	23.4Ad.c.																																																																																																																																										
VDC start up	350V d.c.																																																																																																																																										
VDC MPPT range	200-800V																																																																																																																																										
VAC norm	3-400Va.c.																																																																																																																																										
F AC norm	50Hz																																																																																																																																										
P AC max	33kW																																																																																																																																										
I AC max	47.8Aa.c.																																																																																																																																										
PF	>0.99																																																																																																																																										
Ambient temperature	-25...+60°C (Derating at 45°C)																																																																																																																																										
Ingress protection	IP65																																																																																																																																										
Protective class	Class I																																																																																																																																										
Oversvoltage category	III(MAINS)/II(PV)																																																																																																																																										
Certifications	IEC62109-1/-2																																																																																																																																										
Model Number	CSI-40KTL-GI-HFL																																																																																																																																										
PDC max	45kW																																																																																																																																										
VDC max	1000V d.c.																																																																																																																																										
IDC max(each MPPT)	18/18/18/18Ad.c.																																																																																																																																										
Ipv max short circuit(each MPPT)	23.4Ad.c.																																																																																																																																										
VDC start up	350V d.c.																																																																																																																																										
VDC MPPT range	200-800V																																																																																																																																										
VAC norm	3-480Va.c.																																																																																																																																										
F AC norm	50Hz																																																																																																																																										
P AC max	44kW																																																																																																																																										
I AC max	48.1Aa.c.																																																																																																																																										
PF	>0.99																																																																																																																																										
Ambient temperature	-25...+60°C (Derating at 45°C)																																																																																																																																										
Ingress protection	IP65																																																																																																																																										
Protective class	Class I																																																																																																																																										
Oversvoltage category	III(MAINS)/II(PV)																																																																																																																																										
Certifications	IEC62109-1/-2																																																																																																																																										


The original license holder confirms:

- that the previously certified product and the product referred to on the rating label above are identical in construction including all safety relevant information printed in the user manual or on the product.
- his agreement with issuing the Co-license.
- the enclosure of a German user manual (only relevant for GS-marked products).
- that he enters into an agreement with the Co-license holder according to which the Co-license holder may solely receive certificates for trade names for which the Co-license holder has trademark rights protection and that in case the original license expires or is being cancelled, the Co-license will also be withdrawn.

The original license holder exempts TRLP from any claims that the Co-license holder might raise against TRLP in case of a justified cancellation/withdrawal of the original license.

2017.11.13 宇波

Place and Date


 Company stamp and legally binding signature of original license holder